







## THE PURES


Sleek and virtually knot-free oak parquet

- 3 mm oak top layer
- Sleek and virtually knot-free oak parquet
- Small, healthy knots up to +/- 10 mm and tannin streaks are occasionally permitted
- 99% sapwood-free
- Fairly uniform in color
- UV lacquer finish


14 x 220		
	14 mm	
	3 mm	
	220 X 600-2200 mm	








**DERBY**  
PUR 019 220




**CARDIFF**  
PUR 020 220




**WINCHESTER**  
PUR 021 220


14 x 190		
	14 mm	
	3 mm	
	190 X 600-1900 mm	




**LONDON**  
PUR 019




**LIVERPOOL**  
PUR 020




**MANCHESTER**  
PUR 021








**COVENTRY**  
PUR 023




**NEWCASTLE**  
PUR 025




**LEEDS**  
PUR 022


10 x 152		
	10 mm	
	3 mm	
	152 X 600-1900 mm	








**CHESTER**  
10 PUR 019 150




**SHEFFIELD**  
10 PUR 020 150




**SUNDERLAND**  
10 PUR 021 150


14x120HB		
	14 mm	
	3 mm	
	120 X 600mm	



**YORK**  
PUR 019 HB



**CAMBRIDGE**  
PUR 020 HB



**OXFORD**  
PUR 021 HB

### WOOD DESCRIPTION

<b>WOOD TYPE</b>	Oak Quercus Rubra
<b>SELECTION</b>	AB(C), limited number of "C" planks admitted
<b>KNOTS</b>	Small, healthy knots up to +/- 10 mm and tannin streaks are occasionally permitted
<b>SAPWOOD</b>	99% sapwood-free
<b>COLOR</b>	Fairly uniform in color
<b>EXTRA INFO</b>	End cracks, insect damage, ingrown bark, and mechanical defects are excluded

PUR 019

PUR 020

PUR 021

PUR 023

PUR 025

PUR 022

### DESCRIPTION

Sleek and virtually knot-free oak parquet.  
 Small, healthy knots up to +/- 10 mm and tannin streaks are occasionally permitted & 99% sapwood-free.  
 Fairly uniform in color.  
 End cracks, insect damage, ingrown bark, and mechanical defects are excluded.

### TECHNICAL DATA

<b>WOOD TYPE</b>	Oak Quercus Rubria	
<b>FINISH/ DOP</b>	UV lacquer PUR 019 • PUR 020 • PUR 021 • PUR 022 • PUR 023 • PUR 025	
<b>BEVEL EDGE</b>	GO2 • 14x220 & 14x190 & 10x152 GO4 • 14x120 HB	
<b>TEXTURE</b>	Brushed	
<b>TOP LAYER</b>	3 mm (±0,5 mm)	
<b>CONSTRUCTION</b>	Plank 14 mm • 3-layer poplar Plank 10 mm • multi-layer eucalyptus	
<b>INSTALLATION</b>	T&G - full bonding recommended - floating installation possible	
<b>DIMENSIONS</b>	<b>PLANK</b> • 14 x 220 x 600-2200 mm • 14 x 190 x 600-1900 mm • 10 x 152 x 600-1900 mm	<b>HERRINGBONE</b> • 14 x 120 x 600 mm
<b>PACKAGING</b>	<b>BOX</b> • 14 x 220: 6 layers of which 75% full lengths, max. 25% cut lengths (min. 600 mm) • 14 x 190: 8 layers of which 75% full lengths, max. 25% cut lengths (min. 600 mm) • 10 x 152: 10 layers of which 75% full lengths, max. 25% cut lengths (min. 600 mm) • 14 x 120: 16 full lengths ( 8 right + 8 left ) <b>WEIGHT</b> • 14 x 220 • ± 7,42 kg/m <sup>2</sup> • ± 22,55 kg/box      • 14 x 190 • ± 7,42 kg/m <sup>2</sup> • ± 22,43 kg/box • 10 x 152 • ± 6,70 kg/m <sup>2</sup> • ± 20,67 kg/box      • 14 x 120 • ± 8,52 kg/m <sup>2</sup> • ± 9,81 kg/box	
<b>CONTAINER</b>	• 14 x 220: 26460 kg/container • 1155 box/container • 21 pallets/container • 14 x 190: 22008 kg/container • 960 box/container • 24 pallets/container • 10 x 152: 26784 kg/container • 1296 box/container • 24 pallets/container • 14 x 120: 25120 kg/container • 2560 box/container • 40 pallets/container	
<b>GLOSS LEVEL</b>	5-7%	
<b>STANDARD</b>	European standard EN 14342 : 2013	
<b>MASS DENSITY</b>	600 kg/m <sup>3</sup>	
<b>FIRE RESISTANCE</b>	Cfl-S1	
<b>FORMALDEHYDE EMISSION</b>	E1	
<b>PCP</b>	≤ 0.05ppm	
<b>THERMAL CONDUCTIVITY</b>	0.12W/mK	
<b>DURABILITY CLASS</b>	Class 2	
<b>HUMIDITY DEGREE</b>	6 à 8 % (± 2%)	
<b>FLOOR HEATING</b>	Allowed, subject to compliance with applicable regulations	
<b>MAINTENANCE</b>	See maintenance sheet	

© This technical data sheet was prepared by Floorme.

All information, photos, drawings, tables, and graphs in this sheet are intended to support the product information of Floorme and may only be used in connection with the sale, installation, or specification of Floorme products.

Floorme reserves the right to make changes to the technical data, specifications, images, and product designs at any time and without prior notice.

The photos and illustrations shown, including the displayed wood selections, are for illustrative purposes only and may differ from the delivered product. No rights can be derived from this data sheet.