

DESCRIPTION

Soft and slightly rustic oak parquet.
Healthy knots up to +/- 30 mm, dead knots up to +/- 20 mm & 2 per plank.
Sporadic tannin streaks and limited filled cracks and splits are permitted.
99% sapwood-free.
Limited color variations.
Discoloration, wormholes, and mechanical defects are not permitted.

TECHNICAL DATA

WOOD TYPE	Oak Quercus Rubria
FINISH/ DOP	UV lacquered NAT 019 • NAT 020 • NAT 021 • NAT 022 • NAT 023 • NAT 025
BEVEL EDGE	GO2
TEXTURE	Brushed
TOP LAYER	3 mm (±0,5 mm)
CONSTRUCTION	3-layer poplar
INSTALLATION	T&G - full bonding recommended - floating installation possible
DIMENSIONS	PLANK • 14 x 190 x 600-1900 mm
PACKAGING	BOX • 14 x 190: 8 layers of which 75% full lengths, max. 25% cut lengths (min. 600 mm) WEIGHT • 14 x 190 • ± 7,42 kg/m ² • ± 22,43 kg/box
CONTAINER	22008 kg/container • 960 box/container • 24 pallets/container
GLOSS LEVEL	5-7%
STANDARD	European standard EN 14342 : 2013
FIRE RESISTANCE	Cfl-S1
FORMALDEHYDE EMISSION	E1
PCP	≤ 0.05ppm
THERMAL CONDUCTIVITY	0.12W/mK
DURABILITY CLASS	Class 2
HUMIDITY DEGREE	6-8% (± 2%)
FLOOR HEATING	Allowed, subject to compliance with applicable regulations
MAINTENANCE	See maintenance sheet

© This technical data sheet was prepared by Floorme.
All information, photos, drawings, tables, and graphs in this sheet are intended to support the product information of Floorme and may only be used in connection with the sale, installation, or specification of Floorme products.
Floorme reserves the right to make changes to the technical data, specifications, images, and product designs at any time and without prior notice.
The photos and illustrations shown, including the displayed wood selections, are for illustrative purposes only and may differ from the delivered product. No rights can be derived from this data sheet.