

DESCRIPTION

Sleek and virtually knot-free oak parquet.
Small, healthy knots up to +/- 10 mm and tannin streaks are occasionally permitted & 99% sapwood-free.
Fairly uniform in color.
End cracks, insect damage, ingrown bark, and mechanical defects are excluded.

TECHNICAL DATA

WOOD TYPE	Oak Quercus Rubria	
FINISH/ DOP	UV lacquer PUR 019 • PUR 020 • PUR 021 • PUR 022 • PUR 023 • PUR 025	
BEVEL EDGE	GO2 • 14x220 & 14x190 & 10x152 GO4 • 14x120 HB	
TEXTURE	Brushed	
TOP LAYER	3 mm (±0,5 mm)	
CONSTRUCTION	Plank 14 mm • 3-layer poplar Plank 10 mm • multi-layer eucalyptus	
INSTALLATION	T&G - full bonding recommended - floating installation possible	
DIMENSIONS	PLANK • 14 x 220 x 600-2200 mm • 14 x 190 x 600-1900 mm • 10 x 152 x 600-1900 mm	HERRINGBONE • 14 x 120 x 600 mm
PACKAGING	BOX • 14 x 220: 6 layers of which 75% full lengths, max. 25% cut lengths (min. 600 mm) • 14 x 190: 8 layers of which 75% full lengths, max. 25% cut lengths (min. 600 mm) • 10 x 152: 10 layers of which 75% full lengths, max. 25% cut lengths (min. 600 mm) • 14 x 120: 16 full lengths (8 right + 8 left) WEIGHT • 14 x 220 • ± 7,42 kg/m ² • ± 22,55 kg/box • 14 x 190 • ± 7,42 kg/m ² • ± 22,43 kg/box • 10 x 152 • ± 6,70 kg/m ² • ± 20,67 kg/box • 14 x 120 • ± 8,52 kg/m ² • ± 9,81 kg/box	
CONTAINER	• 14 x 220: 26460 kg/container • 1155 box/container • 21 pallets/container • 14 x 190: 22008 kg/container • 960 box/container • 24 pallets/container • 10 x 152: 26784 kg/container • 1296 box/container • 24 pallets/container • 14 x 120: 25120 kg/container • 2560 box/container • 40 pallets/container	
GLOSS LEVEL	5-7%	
STANDARD	European standard EN 14342 : 2013	
MASS DENSITY	600 kg/m ³	
FIRE RESISTANCE	Cfl-S1	
FORMALDEHYDE EMISSION	E1	
PCP	≤ 0.05ppm	
THERMAL CONDUCTIVITY	0.12W/mK	
DURABILITY CLASS	Class 2	
HUMIDITY DEGREE	6 à 8 % (± 2%)	
FLOOR HEATING	Allowed, subject to compliance with applicable regulations	
MAINTENANCE	See maintenance sheet	

© This technical data sheet was prepared by Floorme.
All information, photos, drawings, tables, and graphs in this sheet are intended to support the product information of Floorme and may only be used in connection with the sale, installation, or specification of Floorme products.
Floorme reserves the right to make changes to the technical data, specifications, images, and product designs at any time and without prior notice.
The photos and illustrations shown, including the displayed wood selections, are for illustrative purposes only and may differ from the delivered product. No rights can be derived from this data sheet.